INFORMAÇÃO DE CONCEÇÃO ECOLÓGICA

Com base no Regulamento (UE) nº 327/2011 da Comissão Europeia, que aplica a diretiva 2009/125/CE do Parlamento Europeu
Aplicável a ventiladores

SODECA, S.L.U. www.sodeca.com

ERP: Características do ponto de eficiência máxima (BEP)

MC	Categoria de medição	**[m³/h]**	Fluxo	**ηe [%]**	Rendimento
EC	Categoria eficiência	**[Pa]**	Pressão estática / Pressão total	**N**	Grau eficiência
VSD	Variador de velocidade	**[RPM]**	Velocidade	**[kw]**	Potência eléctrica
SR	Relação específica				

Modelo	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m³/h]	[Pa]	[RPM]
KIT BOXPDS SMART-II-710-4T-1.5 IE3	Isento ErP									
KIT BOXPDS SMART-II-710-4T-2 IE3	Isento ErP									
KIT BOXPDS SMART-II-710-4T-3 IE3	Isento ErP									
KIT BOXPDS SMART-II-800-4T-3 IE3	Isento ErP									
KIT BOXPDS SMART-II-800-4T-4 IE3	Isento ErP									
KIT BOXPDS SMART-II-800-4T-5.5 IE3	Isento ErP									
KIT BOXPDS SMART-II-900-4T-7.5 IE3	Isento ErP									
KIT BOXPDS SMART-II-900-4T-10 IE3	Isento ErP									
KIT BOXPDS SMART-II-1000-4T-10 IE3	Isento ErP									
KIT BOXPDS SMART-II-1000-4T-15 IE3	Isento ErP									
KIT BOXPDS SMART-II-1000-4T-20 IE3	Isento ErP									